


How the Lake Bonney Wind Farm Met ESCOSA's, NEMMCO's, and ElectraNet's Rigorous Interconnecting Requirements


IEEE PES – Power Toward the Future
Transmission and Distribution
Conference and Exhibition
Dynamic Performance of Transmission Systems
April, 2008



South Australia Transmission Grid and Lake Bonney Wind Farm



Lake Bonney 1 and 2 Wind Farms (240 MW total)



Lake Bonney 1 had no reactive compensation equipment installed.

3


ESCOSA - Wind Interconnection Requirements

- Capable of +/-93% PF at high side of power transformer at full generation.
- Half of PF correction capability shall be dynamic.
- Reactive output proportional to generation level.
- Regulate transmission system voltage.
- Avoid tripping wind farm for nearby transmission grid faults and high voltage (LVRT, HVRT).
- Restore transmission system post fault voltage to a minimum of 90%.

Requirements can be met primarily by installing dynamic and static reactive resources.

4

LB2 159 MW Wind Farm - Sources of Reactive Losses at Full Generation



Bottom Line - Add 47 MVAR to the capacitive reactive compensation target value.

5



Lake Bonney 2 Reactive Compensation Requirements at Full Generation

<u>Target Requirements</u>	<u>Capacitive</u>	<u>Inductive</u>	
• +/-93% PF at 132 kV	63	63	
• Include reactive losses			
- GSU transformer	12	-12	} 47 MVAR
- 33 kV collector grid	11	-11	
- 132-33 kV transformers	<u>24</u>	<u>-24</u>	
Total Reactive Required	110	16	
50% Dynamic	55	8	
50% Non-dynamic	55	8	

6




Lake Bonney 2 Reactive Compensation Resources at Full Generation

Resources	Capacitive	Inductive
• Dynamic VARs (reqmt. is	+55 Cap	-8 Ind)
- Generator VARs	0	0
- D-VAR [®] System (24 x 2.67 O.L.)	64	-64
• Dynamic + Static VARs		
- Generator(+98/-96%PF)	32	-46
- D-VAR System (24 MVAR)	24	-24
- Capacitors (4 x 13.5)	54	0
Total Dynamic + Static	110	-70

7

Lake Bonney 1 and 2 Wind Farms and AMSC's D-VAR[®] Solution



8

D-VAR® System Basics

What are **D-VAR®** Units?

- **D**ynamic **V**ARs... Fully Integrated STATCOMs with proprietary 2.67 times the continuous rating (Overload).
- Instantaneously injects precise amounts of reactive power into a network.
- Can be *seamlessly* integrated with static shunt devices as part of a larger solution.
- Can control the PF of a wind farm's wind turbine generators.



No Trailers

9




Innovative Approaches to Addressing Wind Interconnection Requirements

- Use D-VAR® overload capability to address transient reactive requirements – during both low and high voltage events
- Use slower speed power factor correction capacitors to address post fault voltage issues
- Use turbine variable power factor (PF) output capability to meet PF requirements

10



High Voltage Ride Through PCC and WTG Capability




11



Method of How HVRT Analysis Was Conducted


Analysis of the Impact of the D-VAR® Systems on the Highest WTG Voltage




12



Post Fault Voltage Recovery Simulation Showing Innovative Solution Results




13



Lake Bonney 2 Reactive Compensation Summary

- LVRT met with improved turbine capability.
- D-VAR[®] system met all other dynamic and static interconnection requirements.
- Innovative D-VAR system approach minimizes interconnection investment requirements.
 - D-VAR unit's overload capability used to meet post fault voltage and HVRT requirements.
 - D-VAR system's switches caps and controls variable turbine PF capability to achieve PF and voltage regulation targets.

15



Recent AMSC D-VAR[®] System Installations in Asia



16



Questions?



John Diaz de Leon II
PH 608-828-9179
FX 608-831-5793
jdiazdeleon@amsc.com

