



## Smart Wires

Distributed Series Reactance for Grid Power Flow Control

IEEE PES Chapter Meeting - Jackson, MS

August 8, 2012

*Jerry Melcher*

*Director – Program Management*

*Smart Wires Inc.*



---


**The information and methodologies outlined herein are proprietary, trade secret, and their expression in this document is copyrighted, with all rights reserved to Smart Wire Grid, Inc. Copying or distributing this material without prior written permission is strictly prohibited.**

- **Technology History**
- **Smart Wires Overview**
- **Initial System Impact Simulations**
- **Smart Wires Design**
- **Commercialization Timeline**
- **Wrap-Up**



- **Solutions for Transmission Congestion/Reliability**

- Traditional solutions, such as new lines, are expensive and subject to siting and ROW delays. New lines also deteriorate system utilization.
- Shunt VAR compensation provides voltage support but has limited ability to control power flows in the system.
- Technology solutions such as Flexible AC Transmission Systems (FACTS) are expensive and have been unable to meet utility expectations in terms of reliability and cost.
- Distributed control of line impedances offers a new approach for controlling power flow in networked systems, allowing higher reliability & utilization




---

- **Technology History**

- CEC sponsored the research program in 2006
- TVA and DOE funded the development of a Smart Wires (DSR) prototype
- Georgia Tech NEETRAC initiated the Smart Wires Focus Initiative (SWFI) to work with utilities and the commercialization partner
  - 5 members - Southern, TVA, BG&E, NRECA, Southwire
- SWFI Goals
  - Re-designed for manufacture
  - Lab tested
  - Field testing in Q4 2012
- Smart Wire Grid, has worldwide exclusive license for the technology from Georgia Institute of Technology



## • Smart Wires Technology Overview

- Functions as a current limiter to divert current from the overloaded lines to underutilized ones
- Increases line impedance by injecting a pre-tuned value of magnetizing inductance of the Single-Turn Transformer
- Each module is triggered at a predefined set point to reflect a gradual increase in line impedance
- No communication required and the devices operate autonomously



# CONGESTION EXAMPLE FROM TVA SERVICE AREA


Top 10 Limiting Flowgates



Interchange  
Congestion Areas




- Simplified Four Bus System**






- Initial Results - 1

- Max System Load with and without Smart Wires




- Contingency Condition: Generator Outage



## 39 BUS SYSTEM


- Baseline MW:  
1904 MW
- Increase in ATC  
possible: 638 MW
- Number of modules  
required: 45,000
- Total Control effort:  
378 MVARs  
(8.4kVAR/module)





- Initial Results**

- Increase in line utilization from 59% to 93.3%

**Impact of Smart Wires on Line Utilization**





IEEE PES Chapter Jackson, MS 08/08/2012

*Power flow control for the Grid*



# DESIGN SPECIFICATIONS

---

- **Initial and Current Design Specifications, Ratings**

- Preliminary Alpha Prototype Spec

- Max weight : 150 lb.
  - Conductor size: 336 to 1590 kcmil,
  - Operating voltage level: 115-230 kV
  - Fault current: 63kA
  - Life: 20+ year life w/o maintenance
  - Install: Live line or outaged
  - No corona at operating voltage
  - Environmental: Resistant to salt fog, Aeolian vibration, ice buildup, thermal cycling
  - Conductor impact: No mechanical or thermal conductor degradation
  - Lightning Strike: tested to line BIL
  - Wind loading: up to 150 mph, Communications: Module to ground or SCADA link
- Module rating
    - 10 kVA, 1000 A (50  $\mu$ H per module)
    - One DSR module per phase per mile changes line impedance (138 kV) by roughly 2%





# ALPHA SMART WIRE DEVICE UNDER TEST CORONA TEST WITH 10' GROUND PLANE



Corona inception at 265kV, Extinction 263kV

IEEE PES Chapter Jackson, MS 08/08/2012

*Power flow control for the Grid*






## SWG DEVICE TESTING – CORONA TEST



IEEE PES Chapter Jackson, MS 08/08/2012

*Power flow control for the Grid*




- Impact on Power System Protection**

- Changing the impedance of the line can result in under reach of the distance relay
- By-pass of Smart Wires modules must be faster than the operating time of the protection algorithm
- Distance relays operate by decomposing voltage and current into fundamental components. Operating time can be around 1 cycle (16666  $\mu$ s).
- Smart Wires modules are by-passed in about 40 $\mu$ s. An example is shown below where by-pass has been considered up to about 600  $\mu$ s based on early DSR designs.

3 $\phi$ fault Location	Fault Level	Fault Clearing Time - Nominal Conditions	Fault Clearing Time - With DSR Modules Injecting
25% of line length	31,640 A	15.8 ms	16.2 ms
50% of line length	39,500 A	10.3 ms	10.6 ms
75% of line length	50,000 A	8.3 ms	8.9 ms

## Evaluating available solutions for power flow control

Solution	Cost	Limitation
Transmission Lines	\$500,000/mile, Substation estimate \$80M	<ul style="list-style-type: none"> <li>• Mitigates congestion at one point</li> <li>• Lumpy investment</li> <li>• ROW and siting issues</li> </ul>
HVDC Transmission	\$500,000/mile, Converter Stations \$250M	<ul style="list-style-type: none"> <li>• Point to point solution (merchant lines)</li> <li>• ROW and siting issues</li> </ul>
Sen Transformers	\$100/KVA*	<ul style="list-style-type: none"> <li>• Low reliability due to fault modes</li> <li>• Bulky solution</li> </ul>
Shunt FACTS	\$60-\$120/KVAR	<ul style="list-style-type: none"> <li>• Weak influence on active power flow control</li> <li>• Lower reliability than grid</li> </ul>
Series FACTS	\$60-\$160/KVAR+	<ul style="list-style-type: none"> <li>• Very high installation and operating costs</li> <li>• Bulky solution</li> </ul>
Distributed Series Reactance	\$100/KVAR*	<ul style="list-style-type: none"> <li>• Cannot reduce line impedance without communications</li> </ul>





## Summary

---

- DOE ARPA-E Awardee, contract Apr 2012
- Pilot DSR manufacturing Jun 2012
- Test bed installation planned at TVA - Q4 2012
- Others early 2013

### Contact:

Jerry Melcher  
Director – Program Management  
Smart Wire Grid, Inc.  
1300 Clay Street  
Suite 840  
Oakland, CA 94612-1428  
+1 415-656-7302 C  
+1 415-277-0173 F  
[www.smartwiregrid.com](http://www.smartwiregrid.com)