

Extending the Landsat Legacy: Progress Towards an LDCM Launch

presented to the

Washington / Northern Virginia Chapter

of the

IEEE Geoscience and Remote Sensing Society

by

Jim Irons

LDCM Project Scientist

NASA Goddard Space Flight Center


Greenbelt, Maryland

Goddard Visitor Center


January 21, 2009

History of the Landsat Program

LDCM



Earth's Land Area per Person (in hectares/person)



Why Build the Next One?

LDCM


- **Due to increasing population land cover and land use are changing at rates unprecedented in human history with profound consequences for society**

Food - Water - Shelter - Climate

- **No alternatives to Landsat data continuity**
 - Scale
 - Archive
 - Geographic coverage
 - Data distribution policy
 - Calibration & data quality
- **The need is urgent**
 - Landsat 5 and Landsat 7 are well past design lives
- **A Landsat Data Continuity Mission (LDCM) aligns directly with strategic plans for NASA, national climate change research, and international earth observations**
- **Both the Executive Office of the President and the Congress have mandated a Landsat 7 successor mission**

Landsat 5 Flight Segment

LDCM



Courtesy of Kristi Kline, USGS EROS


Landsat 5 Sun Angle Constraints

LDCM

➤ Nominal coverage at winter solstice

- December 21

Courtesy of Kristi Kline, USGS EROS



Breaking Landsat 5 News

LDCM


➤ **From USGS on Tues., Jan. 20:**

- In October 2007, the mission suffered a major anomaly with one of its two remaining batteries. At that time it wasn't certain that we'd ever be able to resume imaging operations. However, with expert handling from the L5 FOT and some external support, the mission was able to resume some imaging capability, but with a significant reduction in the ability to image a higher latitudes in the 'winter' months. With these limitations, L5 has been unable to image above the Texas state boarder during the winter months. After continuing efforts by the FOT staff, I am pleased to report that on January 19th, L5 will resume full, pre-anomaly imaging capabilities for the Northern Hemisphere ground stations. With this increased capability, we will once again be able to image full CONUS coverage year round. This improvement is also being applied to the 5 other northern ground stations currently operating

Landsat 7 Flight Segment

LDCM

9.5 years of on-orbit operations



Courtesy of Kristi Kline, USGS EROS

ETM+ SLC Failure Impact


IDCM

PRE-SLC FAILURE



3 MARCH 2000

POST-SLC FAILURE



20 SEPTEMBER 2003

Note that the images show partial scenes, from the western edge through the scene center.

Multi-Decadal Archive

LDCM

USGS operates the National Satellite Land Remote Sensing Data Archive at its EROS Center in Sioux Falls, SD


Marketable Scenes through Dec. 31, 2008:

- **ETM+: Landsat 7**
 - 892,051 scenes / 828 TB
 - Archive grows by 260 GB Daily
- **TM: Landsat 4 & Landsat 5**
 - 780,191 scenes / 391 TB
 - Archive Grows by 40 GB Daily
- **MSS: Landsat 1 through 5**
 - 652,173 scenes / 20 TB
 - 20 TB of Data




No other nation is committed to preserving a comparable record of the global land surface

ETM+ Scenes Archived in 2007



- Landsat 7 provides systematic coverage of the global land surface on a seasonal basis via a long term acquisition plan (LTAP)
- No other nation's satellite system is designed or operated to achieve even annual global coverage at the Landsat scale



Data Distribution and Data Policy


LDCM

A NEW ERA

- **USGS EROS has historically distributed Landsat data products to the general public on a non-discriminatory basis at the “cost of fulfilling a user request (COFUR)”**
 - \$600 per Landsat 7 ETM+ scene

- **On April 21, 2008 the USGS released a USGS Technical Announcement stating:**
 - “By February 2009, any Landsat archive scene selected by a user will be processed, at no charge, automatically to a standard product recipe and staged for electronic retrieval.”

Landsat Data Release Schedule


LDCM

Courtesy of Kristi Kline, USGS EROS

2008 Landsat Data Distribution

LDCM

Landsat Data Distribution



■ Landsat Free Downloads ■ Other Landsat Web-enabled Downloads □ Landsat Products Sold

Courtesy of Kristi Kline, USGS EROS





Landsat Data Continuity Mission (LDCM)

LDCM Milestones

LDCM

- **OSTP directed NASA and USGS to implement the LDCM as a “free-flyer” satellite in Dec., 2005**
- **NASA and USGS signed Final Implementation Agreement in April, 2007**
- **Operational Land Imager (OLI) contract was awarded to Ball Aerospace Technology Corporation in July, 2007**
- **Atlas V launch vehicle was selected in Oct. 2007**
- **Spacecraft contract was awarded to General Dynamics Advanced Information Systems in April, 2008**
- **Mission Operations Element (MOE) contract awarded to The Hammers Company in September, 2008**
- **Key Decision Point - B review on September 25, 2008**



Programmatic Status

LDCM

- **LDCM approved to proceed into Project Life Cycle Phase B**
 - Key Decision Point – B (KDP-B) Review (Initial Confirmation) conducted on September 25, 2008
 - As a NASA Category 1 Mission, LDCM requires highest level approval of the Agency Program Management Council chaired by NASA Associate Administrator, Chris Scolese, to initiate each phase of the project life cycle
 - Phase B is the system preliminary design phase following concept studies, Pre-Phase A, and concept and technology development, Phase A
 - LDCM spent **9 years** in formulation, re-formulation, Pre-Phase A, and Phase A


LDCM at KDP-B

NASA Life Cycle Phases	<i>Pre-Systems</i>		FORMULATION		Approval for Implementation			IMPLEMENTATION	
	<i>Acquisition</i>		<i>Systems Acquisition</i>		<i>Operations</i>		<i>Decommissioning</i>		
Project Life Cycle Phases	Pre-Phase A: Concept Studies	Phase A: Concept & Technology Development	Phase B: Preliminary Design & Technology Completion	Phase C: Final Design & Fabrication	Phase D: System Assembly, Int & Test, Launch	Phase E: Operations & Sustainment	Phase F: Closeout		
Project Life Cycle Gates & Major Events	KDP A FAD Draft Project Requirements	KDP B Preliminary Project Plan	KDP C Baseline Project Plan?	KDP D	KDP E Launch	KDP F End of Mission	Final Archival of Data		

KDP-B Process

LDCM

- **In preparation for KDP-B, LDCM conducted a System Requirements Review/Mission Definition Review/Preliminary Non-Advocate Review in May 2008**
 - **System Requirements Review (SRR)**
 - Examines functional and performance requirements defined for the system and ensures the requirements and the selected concept will satisfy the mission
 - **Mission Definition Review (MDR)**
 - Examines proposed requirements, mission architecture, and flow down to all functional elements of the mission to ensure the overall concept is complete, feasible, and consistent with available resources
 - **Preliminary Non Advocate Review (PNAR)**
 - PNAR is conducted as part of the MDR to provide Agency management with an independent assessment of the readiness of the project to proceed to Phase B (mission executable within current cost and schedule)
- **SRR/MDR/PNAR is conducted by a Standing Review Board (SRB)**
 - Independent review panel which conducts system level reviews and follows mission for entire development life cycle
 - **Role of the SRB**
 - Provides expert assessment of technical and programmatic approach, risk posture, and progress against baseline
 - Advisory role to Agency
 - Makes recommendations to improve performance or reduce risk
 - Provides independent cost and schedule assessments



New LDCM Launch Readiness Date

LDCM

➤ **Major finding of SRB**

- Original launch readiness date, July, 2011 was considered excessively aggressive and added risk to the mission
 - “The existing LDCM development schedule is not achievable. There is less than a 20% chance that the July 24, 2011 Launch Readiness Date (LRD) can be achieved.”

➤ **Mission schedules must reflect a 70% confidence level (70% chance of making launch date)**


- Reconciliation of numerous independent schedule assessments and project's own assessment resulted in a retargeted 70% confidence launch date for LDCM

➤ **Through KDP-B Process**

- Retargeted launch date to **December, 2012**
 - Provides appropriate level of confidence
 - Approved by NASA Agency Program Management Council

Dec. 2012 LRD Schedule

LDCM



NASA/USGS Partnership

LDCM


- **The NASA Associate Administrator and the USGS Associate Director of Geography, signed a “Final Implementation Agreement” for LDCM in April 2007**
- **NASA Responsibilities**
 - Development of Space Segment, Launch Segment, and the Mission Operations Element (MOE)
 - Lead mission development as the system integrator and lead the missions systems engineering for all mission segments throughout development, on-orbit check-out, and acceptance
 - Accountable for mission success through on-orbit check-out and acceptance across all mission segments
- **USGS Responsibilities**
 - Development of the Ground System (comprised of the Flight Operations and Data Processing and Archive Segments), excluding procurement of the MOE
 - Lead, fund, and manage the Landsat Science Team
 - Lead LDCM mission operations, after the completion of the on-orbit checkout period

Operational Land Imager (OLI)

LDCM


Contract awarded to Ball Aerospace Technical Corp. (BATC) July 2007
Critical Design Review Completed Oct. 2008

- Pushbroom VIS/SWIR sensor
- Four-mirror telescope with front aperture stop
- FPA consisting of 14 sensor chip assemblies, passively cooled
- Aperture 135 mm
- F number 6.4
- 36 μm / 18 μm detectors (MS / Pan)



Courtesy of BATC

OLI Spectral Bands



System Enhancements

LDCM

Signal-to-Noise Ratios (SNR)

Band	L _{typical} SNR			L _{High} SNR		
	ETM+ Performance	EO-1 ALI Performance (1)	OLI Requirements (2)	ETM+ Performance	EO-1 ALI Performance (1)	OLI Requirements (2)
Coastal Aerosol	N/A	150	130	N/A	340	290
Blue	40	190	130	140	540	360
Green	40	210	100	190	830	390
Red	30	210	90	140	810	340
NIR	35	170	90	250	880	460
SWIR 1	35	200	100	190	1080	540
SWIR 2	30	240	100	140	950	510
Pan	16	190	80	90	550	230
Cirrus	N/A	N/A	50 (3)	N/A	N/A	N/A

- Studies by the Earth Observer-1 (EO-1) Science Team consistently found that Advanced Land Imager (ALI) data offered improved ability to classify images, detect land cover change, and map environmental features and conditions relative to ETM+ data


Focal Plane Consists of 14 Modules

LDCM

- Each Module contains Silicon and HgCdTe detectors mounted on a single readout chip (ROIC)
 - Spectral Filters above the detectors provide separation into bands

Courtesy of BATC

Focal Plane Module (FPM)




Focal Plane Module Uniformity

LDCM

- Need filters and detector responses to be 'the same' ($<0.5\%$) for all 14 FPMs
- Need precise alignment to eliminate clocking or other errors (will be known prelaunch)
 - Eliminate seams and bowing effects

Courtesy of BATC




Calibration Detailed Design Complete

LDCM

Courtesy of BATC


- Calibration Subassembly Consists of Five Subassemblies

- 3 LightShade Assemblies
- 1 Diffuser Assembly
- 1 Shutter Assembly



Exploded View of Calibration Subassembly

- Stim Lamp Assemblies redesigned to increase emitted light and optimize monitoring diode position




Diodes view diffuser instead of housing wall
No direct view of any lamps

OLI Status


LDCM

- **OLI Critical Design Review (CDR) successfully conducted Oct. 27-30**
- **Flight Hardware**
 - Optical Bench completed and delivered to BATC
 - All flight optics completed and delivered to BATC
 - All 14 flight butcher block filters delivered to BATC
 - All 14 EDU focal plane modules completed
 - EDU Instrument Support Electronics box completed
 - EDU Focal Plane Electronics in box-level testing
- **New OLI Baseplate**
 - Baseplate helps 'buffer' the maturity gap between the observatory elements
 - Limits impacts to OLI interface from either changes in spacecraft or TIRS designs
 - Either the baseplate itself and/or the thermal control subsystem (radiator sizes, blanket designs, etc.)
 - Allows work to keep moving on the telescope, the electronics box designs, the focal plane, etc.
 - Allows OLI to be shipped to GD as a whole unit and break down after testing
 - Baseplate (as proposed) will delay OLI delivery from late Oct. 2010 to mid-Dec. 2010




Main Bench Assembly Completed

LDCM



Side View of Bench




Back View of Bench


Courtesy of BATC

Optical Fabrication Complete


LDCM




**Flight Primary Mirror
In Final Inspection**



**Flight Secondary
Mirror in Final Test**



**Flight Tertiary Mirror in Final
Inspection**





**Flight Quaternary Mirror
After Aspheric Shaping**

Courtesy of BATC

Launch Vehicle

LDCM


In September 2007, the Atlas V 401 launch vehicle was selected for LDCM by the Kennedy Space Center.



LDCM Spacecraft

LDCM

Contract awarded to General Dynamics Advanced Information Systems (GDAIS) in April 2008



Courtesy of GDAIS

LDCM Spacecraft

LDCM

COMMUNICATIONS

- S-band to GN/LGN: 1, 32kbps uplink: and 2k, 16k, 32k, or 1 Mbps downlink
- Omni antennas
- TDRSS - SA: 1 kbps return and 2 or 32 Kbps forward
- X-band: 384 Mbps science data

PROPULSION

- Hydrazine blow-down propulsion module
- Eight 22N Redundant Thrusters

GUIDANCE, NAVIGATION & CONTROL


- 2 of 3 star trackers active
- High precision IRU
- Honeywell reaction wheels
- SADA with damper
- 3-axis stabilized
- Zero momentum biased

THERMAL CONTROL

- Passive with heaters
- Constant conductance heat pipes (if needed)

STRUCTURE

- Aluminum primary structure
- Externally mounted components
- Clear instrument FOVs
- Clear instrument radiative paths



ELECTRICAL POWER

- Single wing single axis articulated GaAs solar array provides 4300 W at EOL
- 125 amp-hour NiH_2 battery
- Unregulated 22 V - 36 V power bus
- Two power distribution boxes

COMMAND & DATA HANDLING

- cPCI architecture; RAD750 CPU
- 3.1 Tbit (BOL) solid state recorder
- 265 Mbps peak OLI data transfer
- 26.2 Mbps peak TIRS data transfer
- High rate PB at 384 Mbps

Courtesy of GDAIS

S/C Status

LDCM

- **System Requirements Review (SRR) held Sept. 3-4, 2008**
 - 4 Deficiencies:
 - Requirements Flow Down
 - Open requirements
 - Instrument Interfaces
 - Fault Management
 - GSFC and GD worked together to ensure all SRR deficiencies adequately addressed
 - Major areas of concentration included instrument interfaces (both OLI and TIRS) and resolution of open requirements
- **Delta SRR was successfully conducted on Dec. 17th**
- **Working towards PDR at end of March**

Additional Instruments?

LDCM

- **The spacecraft contract with General Dynamics required that the spacecraft be “scarred” for two additional instruments**
 - **Total Solar Irradiance Sensor (TSIS)**
 - In May 2008, NOAA announced that TSIS is back on NPOESS
 - TSIS no longer an option for LDCM
 - **Thermal Infrared Sensor (TIRS)**
 - Based on continued Congressional and community interest, the LDCM Project is ensuring that a TIRS instrument could still be included on LDCM *(more a little later in this talk)*



Mission Operations Element (MOE)

LDCM

- **NASA awarded The Hammers Company a contract in Sept., 2008 to build the MOE per a reimbursable agreement with USGS**
- **Provides the primary means to control and monitor the spacecraft**
 - Mission planning and scheduling
 - Command and control
 - Monitoring and analysis
 - Flight dynamics
 - Onboard memory management
- **The MOE will be installed in the Mission Operation Centers (MOC's)**
 - Launch MOC will be located at Goddard
- **MOE System Requirements Review (SRR) successfully conducted in Nov.**
- **1st instance of the MOE delivered to GSFC in Nov.**
 - Off-The-Shelf version

Thermal Infrared Sensor (TIRS)

LDCM

- **NASA Authorization Act of 2008 signed into law Oct. 15, 2008**
 - SEC. 205. LANDSAT THERMAL INFRARED DATA CONTINUITY.
 - (a) Plan- In view of the importance of Landsat thermal infrared data for both scientific research and water management applications, the Administrator shall prepare a plan for ensuring the continuity of Landsat thermal infrared data or its equivalent, ... As part of the plan, the Administrator shall provide an option for developing a thermal infrared sensor at minimum cost to be flown on the Landsat Data Continuity Mission with minimum delay to the schedule of the Landsat Data Continuity Mission.
- **The proposed American Recovery and Reinvestment Bill of 2009 includes:**
 - NASA: \$600 million, including \$400 million to put more scientists to work doing climate change research, including Earth science research recommended by the National Academies, satellite sensors that measure solar radiation critical to understanding climate change, **and a thermal infrared sensor to the Landsat Continuing Mapper** necessary for water management, particularly in the western states;

TIRS Status

LDCM

- **Current LDCM baseline design, as approved by NASA Program Management Council, includes only OLI as a single-sensor payload**
- **Based on NASA Program Management Council Direction, the LDCM project at GSFC is ensuring that:**
 - Development of the LDCM spacecraft will not preclude the accommodation of a thermal instrument
 - Accommodation of a thermal instrument does not impact the performance of the Operational Land Imager
- **In parallel with LDCM mission development, thermal instrument and technology risk reduction activities are being pursued**
 - For example, cryogenically-cooled detector technologies are now being evaluated including quantum well infrared photodiodes (QWIP's)

TIRS Status

LDCM

- **A Phase A Study was initiated July 1, 2008.**
 - The Purpose of this study was to proactively investigate the implementation of a Thermal Infrared Sensor for LDCM and provide risk mitigation to the Dec. 2012 LRD.
 - Evaluate / Allocate LDCM requirements.
 - Create a feasible concept design.
 - Assess the programmatic implementation including the schedule and early procurements needed prior to PDR.
 - Begin the instrument development activities.


- **Concept design developed, meets or exceeds the TIRS performance requirements.**
 - System Concept Review held October 17, 2008
 - Independent Review of the current TIRS concept.

TIRS Status

LDCM


- **Development of Quantum Well Infrared Photodetector (QWIP)**
 - ROICs successfully completed both Proton and Gamma Radiation tests.
- **TIRS Instrument implementation targets LDCM launch date of December, 2012.**
 - Instrument delivery planned for December 2011, allowing 10 mos. integration and test at the spacecraft vendor.
 - Current instrument development schedule is detailed for each subsystem and instrument I&T and meets the required delivery date.
- **System Requirements Review scheduled for February 2 and 3rd, 2009**
 - Review all Level 4 and driving level 5 requirements and traceability to Level 3.
 - Review updated concept and system performance against requirements.
- **TIRS PDR scheduled for May 2009**

TIRS Instrument Diagram

LDCM

TIRS Optical Sensor Unit

Spacecraft View

LDCM

TIRS Decision

LDCM

- **Congressional interest in TIRS remains high**
 - Development of the LDCM spacecraft will not preclude the accommodation of a TIRS instrument
 - Accommodation of TIRS does not impact the performance of the Operational Land Imager
- **Project proceeding down path as if TIRS will be there**
 - Directed by Agency PMC at KDP-B to proceed at risk
- **Management of the TIRS instrument currently under purview of LDCM**
 - TIRS team is fully integrated into LDCM team
- **Resolution is expected from the final FY09 appropriations language**
 - Hopefully this spring



LDCM Thermal Requirements

LDCM

Band	Center Wavelength (micrometers)	Spatial Resolution At Nadir (m)	NEΔT Requirements	
			At T _{Typical}	At T _{High}
Thermal 1	10.8	120	0.4K	0.35K
Thermal 2	12.0	120	0.4K	0.35K

- 120 m resolution was felt to be sufficient to resolve most center-pivot irrigation fields in U.S. West - typically 400 to 800 m in diameter
- Landsat satellites provide 16 day repeat imaging -- sufficient for water consumption estimation
- Landsat 4 & 5 TM's provided 120 m thermal images for a single thermal band
- Landsat 7 ETM+ provided 60 m thermal images for a single thermal band
- A two band instrument will enable atmospheric correction so that more accurate surface temperatures can be derived.

Summary

LDCM

- **Good progress towards implementation of the LDCM as a free-flyer - Program has advanced to Phase B**
 - Ball Aerospace Technology Corporation is building the OLI
 - OLI Critical Design Review successfully conducted in Oct., 2008
 - Atlas V launch vehicle was selected in Oct., 2007
 - General Dynamics Advanced Information Systems awarded spacecraft contact in April, 2008
 - Mission Operations Element contract awarded to The Hammers Company in Sept., 2008
 - Ground system development underway at USGS EROS
- **Launch readiness date rescheduled from July, 2011 to December, 2012**
- **Decision to add a TIRS to the LDCM payload is expected following final FY09 NASA appropriations bill**