



# EMCABS

## EMC Abstracts

*Osamu Fujiwara, Associate Editor*

**ANNOUNCEMENT:** *Again with this issue, EMCABS is providing links to the full papers in PDF format to the abstracts shown below. You can access the papers via the on line version of the Fall 2008 Newsletter, EMCABS, at [www.emcs.org](http://www.emcs.org). Please note that in the future, however, the full paper PDFs are limited to the proceedings of the conferences and symposia that were held in technical cooperation with the IEEE EMC Society. For other conferences and symposia, readers may obtain access to the full papers they desire by using the previous methods.*

Following are abstracts of papers from previous EMC symposia, related conferences, meetings and publications.

### EMCABS COMMITTEE

Bob Hunter, Consultant

[r.d.hunter@ieee.org](mailto:r.d.hunter@ieee.org)

Sha Fei, EMC Research Section, Northern Jiatong University, Beijing, China

[emclab@center.njtu.edu.cn](mailto:emclab@center.njtu.edu.cn)

Ferdy Mayer, 7, rue Paul Barruel, F-75015 Paris, France

[ferdymayer@free.fr](mailto:ferdymayer@free.fr)

Maria Sabrina Sarto, Department of Electrical Engineering, University of Rome, Italy

[sarto@elettrica.ing.uniroma1.it](mailto:sarto@elettrica.ing.uniroma1.it)

### "How Can I Get a Copy of an Abstracted Article?"

Engineering college/university libraries, public libraries, company or corporate libraries, National Technical Information Services (NTIS), or the Defense Technical Information Center (DTIC) are all possible sources for copies of abstracted articles or papers. If the library you visit does not own the source document, the librarian can probably request the material or a copy from another library through interlibrary loan, or for a small fee, you can order it from NTIS or DTIC. Recently it became clear that EMCABS were more timely than publications which were being listed in data files. Therefore, additional information will be included, when available, to assist in obtaining desired articles or papers. Examples are: IEEE, SAE, ISBN, and Library of Congress identification numbers.

As the EMC Society becomes more international, we will be adding additional worldwide abstractors who will be reviewing articles and papers in many languages. We will continue to set up these informal cooperation networks to assist members in getting the information or contacting the author(s). We are particularly interested in symposium proceedings which have not been available for review in the past. Thank you for any assistance you can give to expand the EMCS knowledge base. **EMC**

### EMCABS: 01-11-2008

#### MODELING INTERFERENCE COUPLING BETWEEN TWO ORTHOGONAL STRIP LINES ON ADJACENT LAYERS

+ Kenji Araki, ++ Fengchao Xiao, ++ Yoshio Kami, +++ Hemant Bishnoi, and +++ James L. Drewniak

+ Sony Corporation, Japan

++ University of Electro-Communications, Japan

+++ UMR/MST EMC Laboratory, USA

[kenji.araki@jp.sony.com](mailto:kenji.araki@jp.sony.com), [xiao@ice.uec.ac.jp](mailto:xiao@ice.uec.ac.jp),

[kami@ice.uec.ac.jp](mailto:kami@ice.uec.ac.jp), [hbn74@mst.edu](mailto:hbn74@mst.edu), [drewniak@mst.edu](mailto:drewniak@mst.edu)

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 61 - 66.

**Abstract:** In multi-layer circuit boards of modern electronic equipment, signal lines and power distribution traces can be set orthogonally and sandwiched between two reference layers. To evaluate interference between such an intersecting strip line geometry, a lumped mutual capacitance model is proposed. Determining the scalar potential due to an assumed line charge at the intersection of the orthogonal traces leads to the distributed mutual capaci-

tance between two lines. The results show that for typical printed circuit board geometries, the mutual capacitance can be approximated as a lumped element at the intersection of the two orthogonal strip line geometries. The proposed model is verified by comparing the experimental and the computed results.

**Index terms:** Multi-layer circuit boards, orthogonal strip lines, interference coupling model, lumped mutual capacitance.

### EMCABS: 02-11-2008

#### ANALYSIS OF A PCB-CHASSIS SYSTEM INCLUDING DIFFERENT SIZES OF MULTIPLE PLANES BASED ON SPICE

+ Naoki Kobayashi, ++ Todd Hubing and + Takashi Harada + NEC, System Jisso Research Laboratories, Kanagawa, Japan ++ Clemson University, Holcombe Department Electrical & Computer Engineering, Clemson, SC, USA

[n-kobayashi@aj.jp.nec.com](mailto:n-kobayashi@aj.jp.nec.com), [t-harada@bl.jp.nec.com](mailto:t-harada@bl.jp.nec.com), [Hubing@CLEMSON.EDU](mailto:Hubing@CLEMSON.EDU)

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 97 - 102.

Comprehensive  
Electromagnetic  
Solutions

FEKO



Where ideas are brought to life!



- MLFMM
- FEM/MoM
- UTD
- PO
- GO

## 3D EM SIMULATION SOFTWARE

for real life problems, with FREE 45 days evaluation



Antenna Placement



Antenna Design



Dielectric Bodies



EMC



Microstrip Antennas



RF & Microwave

[www.feko.info](http://www.feko.info)

*Abstract:* This paper describes the SPICE modeling of multiple plane structures where the inner layer planes have different shapes than the outer layer planes. These structures are often seen in a printed circuit board (PCB), or the space between a PCB and metal chassis. First, a SPICE model is proposed for these structures using two dimensional ladder networks and ideal transformers. Next, the model is expanded to structures including vertical connecting conductors, such as vias in a PCB and grounding posts connecting a PCB to a metal chassis. Coupling properties inside a PCB are calculated using the SPICE model and shown to be consistent with experimental data. Furthermore, radiated emissions from a PCB-chassis system are also calculated based on the SPICE and equivalent magnetic current source models. The results are consistent with experimental data to show the changes in radiated EMI due to the locations of grounding posts.

*Index terms:* SPICE models, multiple planes, two dimensional ladder network, ideal transformer, power bus resonance, chassis connections, grounding posts, equivalent magnetic current source, radiated EMI from PCBs.

---

**EMCABS: 03-11-2008**

#### USE OF REVERBERATION CHAMBER TO SIMULATE THE POWER DELAY PROFILE OF A WIRELESS ENVIRONMENT

+, ++ E. Genender, ++ C. L. Holloway, ++ K. A. Remley, ++ J. Ladbury, ++ G. Koepke and + H. Garbe

+ Leibniz University of Hannover, Institut fuer Grundlagen der Elektrotechnik und Messtechnik, Appelstrasse 9A, 30167 Hannover, Germany

++ National Institute of Standards and Technology (NIST), 325 Broadway, Boulder, CO 80305, USA

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 219 - 224.

*Abstract:* Multipath propagation environment effects, such as frequency-selective fading, have a strong impact on the quality of a wireless channel. For example, multipath can impact bit error rate (BER) differently from Gaussian noise. For testing wireless devices/systems in these multipath environments it is imperative to have a reliable, controllable, and statistically repeatable measurement facility. The purpose of this paper is to illustrate how the reverberation chamber can be used to simulate different multipath propagation environments. Channel characteristics such as power-delay profile, RMS-delay spread, and the Rician K-factor are examined. Results for different chamber configurations (e.g., loading of the chamber, antenna positions, etc.) are compared and their effects discussed. Results achieved inside a chamber are compared with those obtained in an actual industrial environment.

*Index terms:* Delay spread, multipath propagation, power delay profile, reverberation chamber, Rician K-factor, wireless communications, wireless environment.

---

**EMCABS: 04-11-2008**

#### MAXIMUM RATES OF FREQUENCY SCANNING AND MECHANICAL OR ELECTRONIC STIRRING FOR DISTORTIONLESS SIGNAL GENERATION INSIDE ELECTROMAGNETIC REVERBERATION CHAMBERS

Luk R. Arnaut

Time, Quantum and Electromagnetics Team, National Physical Laboratory Hampton Road, Teddington TW11 0LW, United Kingdom

luk.arnaut@npl.co.uk

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp.225 - 228.

*Abstract:* We present upper bounds for the rates of frequency scanning and mechanical or electronic stirring inside a reverberation chamber. The bounds are obtained by imposing quasi-stationary of the field to hold, allowing avoidance of nonlinear distortion of the analog or digital excitation (test) signal injected into the chamber. The interior field is represented as a dynamic stochastic process causing random hybrid modulation of the excitation field.

*Index terms:* EMC measurements, reverberation chambers, quasi-stationary, frequency scanning, mode stirring.

---

**EMCABS: 05-11-2008**

#### NUMERICAL ANALYSIS OF ELECTROMAGNETIC FIELD DISTRIBUTIONS IN A TYPICAL AIRCRAFT

+ Takashi Hikage, + Toshio Nojima, ++ Manabu Omiya and +++ Kazuo Yamamoto

+ Graduate School of Information Science and Technology, Hokkaido University Sapporo, Japan

++ Information Initiative Center, Hokkaido University Sapporo, Japan

+++ Electronic Navigation Research Institute Independent Administrative Institution Tokyo, Japan

hikage@wtmc.ist.hokudai.ac.jp, nojima@wtmc.ist.hokudai.ac.jp, omiya@iic.hokudai.ac.jp, yamamoto@enri.go.jp

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 303 - 307.

*Abstract:* The purpose of this study is to develop an accurate and reliable estimation method of electromagnetic field distributions in practical environments including passengers. However, comprehensive measurements in an actual environment are very costly and it is difficult to carry them out precisely. In this paper, large-scale numerical simulations are carried out to examine the electromagnetic fields excited by the 2.45 GHz wireless LAN terminal inside an aircraft. We used a typical aircraft model and employed the FDTD technique and a supercomputer to estimate the field distributions inside the whole area of the cabin. A large-scale parallel computing technique based upon several node partitions of a supercomputer was used because of its memory and speed capabilities. It is able to give us a good perspective within a reasonable computation time. Furthermore, a simplified histogram estimation method for electric field strength in the cabin was employed to deal with the complicated EMF distributions inside the cabin including passengers.

*Index terms:* Wireless LAN, aircraft, large-scale FDTD analysis, fields histogram estimation.

---

**EMCABS: 06-11-2008**

#### MULTIPOLAR EXPANSION SENSORS FOR NEAR FIELD CHARACTERIZATION

B. Vincent, O. Chadebec and J. L. Schanen

G2ELab, UMR 5269-CNRS-INPG-UJF  
ENSIEG, B.P.46, 38402 St Martin  
d'Herès cedex

benjamin.vincent@g2elab.inpg.fr, olivier.chadebec@g2elab.inpg.fr, jean-luc.schanen@g2elab.inpg.fr

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 319 - 322.

**Abstract:** This paper introduces a new generation of magnetic field sensors, based on the spherical harmonics decomposition concept. The measurement principle is similar to a spatial filtering; according to the coil shape, the sensors are just sensitive to a specific component of the multipolar expansion. Five coil shapes are determined in order to account for the first two orders of the harmonic decomposition. The way of determining the coil shape is first explained, and a validation is proposed using finite element software.

**Index terms:** Coils electromagnetic sensors, near field measurements, multipolar expansion, radiated EMC, radiated electromagnetic sources characterization.

EMCABS: 07-11-2008

#### CLASSIFICATION OF ELECTROMAGNETIC EFFECTS AT SYSTEM LEVEL

Frank Sabath

Bundeswehr Research Institute for Protective Technologies and NBC-Protection, Munster, Germany

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 509 - 513.

FrankSabath@bwb.org

**Abstract:** High-Power Electromagnetic (HPEM) environments are capable of causing effects like malfunctions, performance degradation, interferences, and destructions in electronic and electrical systems. Due to the large plurality of effects, a scientific and systematic discussion requires classifications, which abstract the essential information. This paper presents a systematic classification of electromagnetic (EM) effects. The presented system enables an assessment and comparison of EM effects at system level.

**Index terms:** High-power electromagnetics, effects, susceptibility, intentional electromagnetic interference, classification.

EMCABS: 08-11-2008

#### MOM-BASED ANALYSIS OF THE IMMUNITY OF MARINE EQUIPMENT IN A CONTROL CABINET OF CRUISE AND CONTAINER VESSELS AGAINST 2.4-GHZ WLAN APPLICATION

+ Miguel Astner, ++ Tobias Pilsak, + Heinz-D. Breuns, ++ Jan Luiiken ter Haseborg and + Hermann Singer  
+ TU Hamburg-Harburg, Institute of Electromagnetic Theo-

ry Hamburg, Germany

++ TU Hamburg-Harburg, Institute of Measurement Technology and Electromagnetic Compatibility Hamburg, Germany  
M.Astner@tu-harburg.de, Bruens@tu-harburg.de, Singer@tu-harburg.de, Pilsak@tu-harburg.de, terHaseborg@tu-harburg.de  
Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp.581 - 586.

**Abstract:** In this contribution, a typical control panel is investigated. The structure is assembled on bridges of modern ships. Numerical results are presented for the excitation by means of a WLAN antenna. The applied technique was the method of moments based upon a combination of the adaptive-cross approximation and singular value decomposition (ACA/SVD) solver to deal with the exhaustive computational requirements due to the large extension of the panel in terms of wavelength.

**Index terms:** Method of Moments, MoM, fast solver, ACA, SVD, wireless LAN, WLAN, IEC 60945.

EMCABS: 09-11-2008

#### EFFECTS OF SHIELDING ENCLOSURES ON THE BREAKDOWN FAILURE RATE OF ELECTRONIC EQUIPMENT

Helge Herlemann, Sven Fisahn, Michael Koch and Heyno Garbe

Leibniz Universität Hannover, Institute of the Basics of Electrical Engineering and Measurement Science Hannover, Germany

## Ferrites by Fair-Rite Products

### Three Key Elements: One Clear Choice



Fair-Rite manufactures a comprehensive line of ferrite components for EMI Suppression, Power Applications, and Antenna/RFID Applications. We have an experienced team of engineers to assist you with new designs. Fair-Rite is the first US soft ferrite manufacturer to receive ISO/TS 16949 : 2002 certification.

Please visit [www.fair-rite.com](http://www.fair-rite.com) to view our online catalog and find a variety of new help tools and search features. You can also easily contact applications engineers, sales representatives, and local distributors. Be sure to bookmark our website as your source for ferrite information.



**Fair-Rite Products Corp.**  
**Your Signal Solution®**



PO Box J, One Commercial Row, Wallkill, NY 12589-0288 USA  
Phone 888-324-7748 / 845-895-2055 / Fax 888-337-7483  
[ferrites@fair-rite.com](mailto:ferrites@fair-rite.com) / [www.fair-rite.com](http://www.fair-rite.com)

herlemann@ieee.org

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 611 - 616.

*Abstract:* As a criterion of quality of a shield regarding its ability to protect electronic equipment against electromagnetic pulses, the breakdown failure rate of operating test equipment with and without the shield can be compared. In this contribution, the shielding behavior of cubical shields with varying rectangular slots against ultra wideband pulses of double exponential wave form is studied. It is found that applying the shield may have the effect that electronic equipment becomes even more vulnerable to pulses due to resonance effects inside the enclosure. The results of these examinations in time domain are compared to results in frequency domain which can be found in publications.

*Index terms:* UWB-pulses, shielding effectiveness, rectangular enclosure with rectangular aperture.

---

#### EMCABS: 10-11-2008

#### GENERALIZED PEEC METHOD BASED ON DYADIC GREEN'S FUNCTIONS IN TIME AND FREQUENCY DOMAIN

Sergey V. Kochetov, Marco Leone

Otto-von-Guericke University Magdeburg, Institute for Fundamental Electrical Engineering and Electromagnetic Compatibility Magdeburg, Germany

kochetov@ovgu.de

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp.647 - 652.

*Abstract:* This paper presents a novel concept for time- and frequency-domain modeling with the PEEC method (DGF-PEEC), which is based on the mixed potential integral equation (MPIE) with dyadic Green's functions. Such models provide exact full-wave semi-analytical solutions for an arbitrary interconnection system; on the other hand, they are represented in a circuit form and, thus, can be implemented in common circuit simulators. The paper derives a general DGF-PEEC formulation that can be applied to all types of MPIE with dyadic Green's functions. Based on this concept, the PEEC model for interconnections in layered media is developed and verified with the help of a MoM code and by measurements as well.

*Index terms:* PEEC, dyadic Green's functions, time domain analysis, striplines.

---

#### EMCABS: 11-11-2008

#### BAND-LIMITATION EFFECT ON STATISTICAL PROPERTIES OF CLASS-A INTERFERENCE

+ Yasushi Matsumoto, + Kaoru Gotoh and ++ Kia Wiklundh  
+ National Institute of Information and Communications Technology, Koganei, Tokyo, Japan

++ Swedish Defence Research Agency Linköping, Sweden  
ymatsumoto@ nict.go.jp, k\_gotoh@ nict.go.jp, kia.wiklundh@foi.se

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp.715 - 720.

*Abstract:* The effect of band limitation on the statistical properties of Middleton's Class A noise model is investigated. It is found that a uniformly weighted sum of statistically independent and identically distributed Class A random variables becomes a new Class A random variable with reduced impulsiveness. It is also found that band limited noise becomes Class A noise if the impulse response of the filter has a rectangular envelope waveform. Since matched filters employed by DS-SS (direct sequence spread spectrum) or OFDM (orthogonal frequency division multiplex) systems usually satisfy the above condition, the results can be widely applied to the evaluation of the error probability of signal detection in such communication systems subjected to Class A interference.

*Index terms:* Electromagnetic interference, nongaussian noise, amplitude probability distribution, Class A.

---

#### EMCABS: 12-11-2008

#### EVALUATION OF SENSITIVITY OF DIGITAL TV RECEIVER SUBJECTED TO INTRASYSTEM INTERFERENCE

+ Kaoru Gotoh, + Yasushi Matsumoto, ++ Hiroshi Tsutagaya and ++ Satoshi Kazama

+ National Institute of Information and Communications Technology, Tokyo, Japan

++ TAIYO YUDEN Co., Ltd. Gunma, Japan

k\_gotoh@nict.go.jp, ymatsumoto@nict.go.jp, tsutah@jty.yuden.co.jp, kazama@jty.yuden.co.jp

Proceedings of the 8th International Symposium on Electromagnetic Compatibility, Hamburg, Germany, September 8-12, 2008, pp. 727 - 730.

*Abstract:* This study demonstrates that the sensitivity of the orthogonal frequency division multiplexing (OFDM) digital television (DTV) receiver particularly for mobile reception subjected to intra-system interference is possible to be estimated from the amplitude probability distributions (APDs) of the interfering noise measured with the subcarrier bandwidth of the DTV receiver. It was found that the bit error probability (BEP) after error correcting of victim DTV receiver is approximately estimated from APD of interfering noise by using the coding effect in the presence of Gaussian interference. The experimental result showed that the coded BEP performance was highly correlated with the sensitivity of the mobile DTV receiver.

*Index terms:* Component, digital broadcasting, one-segment broadcasting, ISDB-T, reception sensitivity, amplitude probability distribution.

EMC