

# **IEEE Switchgear Committee Meeting Pittsburgh, PA**

---

## ***Monitoring and Diagnostics for High Voltage Circuit Breakers: The Condition Monitoring Unit (CMU)***

***November 11, 1999***

*Aftab H. Khan  
Technology Director  
ABB High Voltage Switchgear Division  
Greensburg, PA*

# Reliability Centered Maintenance


---

- | Example: Commercial Aircraft Industry
  - DC 8 required 339 overhaul items, DC 10 required 7.
  - Greater than 50% reduction in spare parts inventory
  - **Cost reductions achieved with no reduction in reliability**

# Reliability Centered Maintenance

---


## | DECISION TREE





# Circuit Breaker Failures

---

**MAJOR FAILURES\***



**MINOR FAILURES\***



\* 1994 CIGRE WG13.06 Study of HV Single Pressure SF6 Circuit Breakers

# Objectives of Monitoring

---

- | Utilize Design Know-How To:
  - Identify impending failures (direct & indirect impacts)
  - Reduce routine maintenance
- | Reduce Total Cost of Ownership

# Condition Monitoring Unit

---

## **Diagnostic Feature**

- | Mechanical System Condition (operating mechanism)
- | Interrupter Condition
- | SF<sub>6</sub> Gas System Condition
- | Control Circuit Condition


## **Sensors (monitored quantity)**

- | Optical Travel Transducer (Operating Time, Speeds), Shunts (Charging Motor Current & Voltage)
- | Secondary CT's (interrupted current, arcing time)
- | Pressure sensor, Temperature sensor (SF<sub>6</sub> Gas Density)
- | Trip & Close Coil Availability, Heater Current Monitoring

# Travel Sensors

---


## | *Optical Sensors with Metal Comb*



# Current Sensors

---

- | ***Split-Core: Phase Currents***
- | ***Doughnut: Heater Currents***






# Diagnostics Approach

---


- | ***On-line*** vs. off-line monitoring
- | ***Data analysis*** vs. data collection
  - e.g. interrupter wear calculation



# Diagnostics Approach (cont.)


---

- e.g. Operating mechanism charging system



# CMU Installation (<242 kV)

---



# CMU Installation (362-550 kV)

---



# CMUControl Software

---


- Graphical display of CMU data
- Modem dial-up capabilities (MODBUS for network connections)
- Automatic setpoint creation for commissioning tests
- Loading and updating CMU software

# CMU Control




Present Conditions Alarm Summary Events **Contact Travel** Auxiliary Switches Phase Currents Hi Res. Ph. Cur. Setup


Event #2, Pole #1



Event #2, Pole #2



Event #2, Pole #3



Overall Condition:

**NORMAL**

Data Downloaded:

Date: 2/19/99

Time: 12:21:24

Software Versions:


CPU: App. 1.35

Aux: App. 1.34

Pole: App. 1.31

Contact CMU

Request CMU Reports




Finished replaying.

# CMU Control




Present Conditions Alarm Summary Events Contact Travel Auxiliary Switches **Phase Currents** Hi Res. Ph. Cur. Setup


Event #2, Pole #1



Event #2, Pole #2



Event #2, Pole #3



Overall Condition:

**NORMAL**

Data Downloaded:

Date: 2/19/99

Time: 12:21:24

Software Versions:


CPU: App. 1.35

Aux: App. 1.34

Pole: App. 1.31

Contact CMU

Request CMU Reports




Finished replaying.

# CMU Control




Present Conditions Alarm Summary Events Contact Travel Auxiliary Switches Phase Currents Hi Res. Ph. Cur. Setup


Event #2, Pole #1



Event #2, Pole #2



Event #2, Pole #3



Overall Condition:  
**NORMAL**

Data Downloaded:

Date: 2/19/99

Time: 12:21:24

Software Versions:


CPU: App. 1.35

Aux: App. 1.34

Pole: App. 1.31

Contact CMU

Request CMU Reports



Finished replaying.